

AQUAMAX START RANGE

- High-performance motor
- Electronically adjustable (except Aquamax 2000)
- Pumps coarse debris up to 8 mm in size*
- Ball joint with infinite pivot range facilitates hose connection
- Including special hose adapter with threaded collar for connecting hose sizes 3/4", 1", 1 1/4" and 1 1/2"
- 3 + 2 year guarantee



Aquamax	2000	3500	5500	8500
Dimensions in mm (ØxH)	234 x 173 x 126		297 x 159	
Power consumption in watt	32	53	75	110
Max. flow rate (l/min.)	33	60	92	135
Max. flow rate (l/h)	1980	3600	5520	8100
Max. head height (m)	2.0	1.6	2.5	3.2
Outlet connection in inches	1"		1 1/2"	
Inlet connection in mm/inches	Ø 25 mm		1 1/2"	
Filter surface in cm ²	300		810	
Weight in kg with 10 m cable	2		4	

All filtration and watercourse pumps have a rated voltage of 220-240 V/50Hz. The full guarantee of 3 years can be extended by an additional 2 years on request for a total of 5 years. The pumps are also suitable for use in swimponds and bathing ponds.



The Aquamax model numbers are based on the »max. litres per hour« value.

AQUAMAX Eco PRO RANGE

- Energy-efficient motor with innovative electric control for optimisation of the efficiency level, saves up to 40% energy
- An additional 20% saving in energy is possible thanks to the newly developed Seasonal Flow Control (SFC – for Aquamax ECO 12000/16000)
- Flow-optimised impeller guarantees maximum hydraulic pump performance and improved displacement of coarse debris
- Large surface filter housing allows debris such as vegetation or koi waste up to 10 mm in size to pass through
- Ball joint with infinite pivot range facilitates hose connection
- Second mechanically adjustable inlet for connection of skimmer/satellite filter for skimming surfaces or pond water
- Fully capable of withstanding winter conditions thanks to intelligent frost protection technology
- Environmental Function Control (by OASE) protects against dry-run and blocking
- Mechanically adjustable
- Suitable for use in swimponds and bathing ponds



Aquamax Eco	4000	6000	6000/ 12 V**	8000	12000	16000
Dimensions in mm (L x W x H)	350 x 284 x 163					
Rated voltage	220 - 240 V / 50 Hz		12 V	220 - 240 V / 50 Hz		
Power consumption in watt	50	60	55	80	130	170
Max. flow rate (l/min.)	65	100	100	133	200	266
Max. flow rate (l/h)	4000	6000	6000	8000	12000	16000
Max. head height (m)	3.2	3.6	3.2	4.0	5.2	5.6
Filter surface in cm ²	950 cm ²					
Weight in kg with 10 m cable	4.3	4.3	8.3	4.3	5.6	5.6

All Aquamax Eco pumps have a 2" connection thread on the outlet side and 1 1/2" connection thread on the inlet side with hose connecting pieces for hoses ranging from 1" to 1 1/2" inches and a cable length of 10 m. The full guarantee of 3 years can be extended by 2 additional years to 5 years. In addition the pumps are suitable for use in swimponds and bathing ponds; even the 12V pump is suitable for swimponds.

** Only mechanically adjustable